

BASE PRICING:

FDC - C91	\$155.00
FDC - C21	\$155.00



(1/16 DIN)	FDC - C91	<input type="checkbox"/>						
(1/32 DIN)	FDC - C21	<input type="checkbox"/>						

Schedule A

1 2 3 4 5 6 7

1. POWER INPUT

4:	90-250VAC 50/60 HZ	N/C
5:	11-26VAC/1VDC	\$15.00
9:	Special Order	

2. SIGNAL INPUT

1:	Thermocouple: J,K,T,E,B,R,S,N,L RTD: PT100DIN & JIS	N/C
3:	0-1VDC	\$15.00
4:	0-5VDC	\$15.00
5:	1-5VDC	\$15.00
6:	4-20mA	\$15.00
7:	0-20mA	\$15.00
8:	0-10VDC	\$15.00

3. OUTPUT 1

0:	None	N/C
1:	Relay 2A/240VAC resistive (SPST)	N/C
2:	SSR Drive 5VDC @30mA	N/C
3:	4-20/0-20mA linear, isolated, max load 500 ohms	\$28.00
4:	1-5/0-5VDC linear, isolated, min impedance 10K ohms	\$28.00
5:	0-10VDC linear, isolated, min impedance 10K ohms	\$28.00
6:	Triac 1A/240VAC	\$28.00
C:	SSR Drive 14VDC @40mA	\$28.00
9:	Special Order	

4. OUTPUT 2 / Alarm (control PID Cool only)

0:	None	N/C
1:	Form A Relay 2A/240VAC resistive (SPST)	\$12.00
2:	SSR Drive 5VDC @30mA	\$12.00
3:	4-20/0-20mA linear, isolated, max load 500 ohms	\$28.00
4:	1-5/0-5VDC linear, isolated, min impedance 10K ohms	\$28.00
5:	0-10VDC linear, isolated, min impedance 10K ohms	\$28.00
6:	Triac 1A/240VAC	\$28.00
7:	Transmitter Power Supply 20VDC/25mA (isolated)	\$28.00
8:	Transmitter Power Supply 12VDC/40mA (isolated)	\$28.00
9:	Transmitter Power Supply 5VDC/80mA (isolated)	\$28.00
A:	RS485 Modbus RTU (C91 only)	\$75.00
C:	SSR Drive 14VDC @40mA	\$28.00
D:	Retransmission 0-20/4-20mA (C91 only), isolated, 500 ohm load	\$90.00
E:	Retransmission 0-5/1-5VDC (C91 only), isolated, 10k ohm load	\$90.00
F:	Retransmission 0-10VDC (C91 only), isolated, 10k ohm load	\$90.00
B:	Special Order	

5. COMMUNICATIONS

0:	None	N/C
1:	RS-485 Modbus RTU	\$75.00
2:	RS-232 Modbus RTU	\$75.00
3:	Retransmission: 0-20/4-20mA, isolated, 500 ohm load min	\$90.00
4:	Retransmission: 0-5/1-5VDC, isolated, 10K ohm load min	\$90.00
5:	Retransmission: 0-10VDC, isolated, 10K ohm load min	\$90.00
9:	Special Order	

6. DISPLAY COLOR

0:	Red	N/C
1:	Green	N/C

7. SPECIAL ORDER

Leave Blank unless assigned a specific 2-character Special Order Code

Note: The last digit (code 7) is typically left blank.

Output 2: Configurable for PID cool (requires output #1 to be PID):
PID cool outputs: Relay, SSR or mA/VDC.

DIN Rail Mount Adapter models DRA-16 & 32 refer to page 37



File#: E197216

209463



EC & RoHS Compliant

P.O. Box 1196 · Bridgeview, IL 60455
 888.751.5444 Sales · 888.307.8014 Fax
 Technical Support: 866.342.5332
<http://www.futuredesigncontrols.com>